



ADDENDUM NO. 1, DATED 08/10/2016

RE: TO Furnish and Deliver Custom Banners and Supplies for
Southeastern Louisiana University and the Admissions Department.

Dear Bidder,

TO AMEND: THIS ADDENDUM IS TO PROVIDE CLARIFICATION ON THE PRODUCT
SPECIFICATIONS, USE, AND EXPECTED DELIVERY DATE.

Question: What is the expected delivery date?

Response: September 30, 2016.

Question: What fabric is required and its thickness (weight)?

Response: Must be Sunbrella Marine Fabric Forest Green - 9oz/sqft

Question: What is the expected life use of the banners?

Response: The expected use is 3 to 5 years

Question: What type bracket is required?

Response: The bracket offered must be equal to or better than BannerFlex KBW D3. Highest level of durability and performance; no moving parts; Comprised of the main bracket casting and the fiberglass arm with rod casting. 13/16" round fiberglass bracket arm provides flexibility while maintaining strength and increasing banner longevity.

Question: Request for artwork to be provided prior to bidding?

Response: Artwork will not be provided prior to bidding. Artwork will be provided to the awarded bidder.

Question: How many colors are to be used on the banner?

Response: Two colors

Request for Clarification on the Banding Roll?

Response: See Product Specifications attached.

Request for Clarification on Banding Buckles?

Response: See Product Specifications attached.

Attachments (2)

Sincerely,



Richard Himber
Director of Purchasing

cc: File

Addendum Acknowledged By:

Name of Business: _____

Signature: _____ Date: _____



3/4" X 100'

TOOL-APPLIED BANDING ROLL

The bright annealed finish sets the standard in banding, clamping and fastening with a combination of high strength and quality appearance. Offers good resistance to oxidation and many moderate corrosive agents.

Bright annealed finish sets the standard in banding clamping and fastening with a combination of high strength and quality appearance. Recommended for use with both the standard and double banding applications are shown on the KBW Banding Guideline Chart. Available in natural stainless steel or black powder coat.

Details

- Stainless steel offers good resistance to oxidation and many moderate corrosive agents
- Installs easily with banding tool
- Utilized in general use banding application
- Recommended accompaniment with Ear Lokt style buckles



Banding Buckles – 100 per box

Banding Buckles can be used with many types of $\frac{3}{4}$ tool-applied stainless steel banding providing superior fastening strength.

Made of stainless steel to ensure optimal performance and superior fastening strength, banding buckles are available in packages of eight (8) or boxes of 100. Four buckles are needed per pole and suggested to use with $\frac{3}{4}$ tool-applied banding.

Details

- Stainless steel; Ear-Lokt style buckles
- Resistant to oxidation and many moderate corrosive agents
- For use with single or double wrapping
- For use with $\frac{3}{4}$ tool-applied banding and banding tool